

## DESCRIPTION

FSP400-701UH is an industrial level of switching power supply. The power supply comes to offer the total power capacity up to 400 Watts, and uses unique active PFC (Power Factor Correction) circuit design with its high-load electrical components, makes it to be perfectly used in an industrial environment. In addition, with its full range of input and output electrical features, the power supply is ideally the best choice for server, workstation, communication or any other automation applications to use. The product also complies with the latest safety and EMC standards, which is perfectly to meet various regulations worldwide.



## APPLICATION

For standard, advanced server, NAS, storage, and industrial power system.

## FEATURES

- 85 Plus Bronze
- Low Ripple & Noise
- Output over voltage protection
- Short circuit protection on all outputs
- Resettable power shut down
- Dual +12V output (+12V1,+12V2)
- INTERNAL 4 cm fan
- 100% burn-in under high ambient temperature(50°C)
- Vacuum-impregnated transformer
- MTBF:100K hours at 25°C
- 100% Hi-pot tested
- Line input fuse protection

## WATTAGE

**Wattage:** 400W

## DIMENSION

**Dimension:** 220mm(L) x 100mm(W) x 40.5mm(H)

## PRODUCT HIGHLIGHT

**Efficiency Level:** 80 Plus Bronze  
**Altitude:** 5000M

## INPUT SPECIFICATION

**Input Range:** 90-264 Vac  
**Input Frequency:** 47-63 Hz  
**Input Current:** 115V@ 8.0 Amps-rms maximum  
230V@ 4.0 Amps-rms maximum

## GENERAL SPECIFICATION

**Efficiency:** 85% 230VAC  
**Voltage:** +3.3V, +12V, +5V, +5SB: ±5%  
**Regulation:** -12V: ±10%


### \*Output Voltage and Current Rating

	+3.3V	+5V	+12V1	+12V2	+12V3	-12V	+5Vsb
<b>Ripple-Noise(R-P) mV</b>	50mV	50mV	120mV	120mV	120mV	120mV	50mV
<b>Regulation Load %</b>	±5%	±5%	±5%	±5%	±5%	±10%	±5%
<b>Output Max.(A)</b>	20A	20A	16A	16A	16A	0.5A	3A
<b>Output Min.(A)</b>	0.5A	1A	0.5A	1A	1A	0A	0A

## NOTES

- 5V, 3.3V, 12V, -12V Will have the regulation to 10% when all load take off.
- The +3.3V and +5V total output shall not exceed 120 watts.
- The 12V1 and 12V2 and 12V3 total output shall not exceed 30A.
- The total output shall not exceed 400 watts

## MECHANICAL SPECIFICATION



## SAFETY STANDARD APPROVAL



## OUTPUT SPECIFICATION

**Hold up Time:** 115V/60Hz 16mSec.  
Minimum@50% Load,  
230V/50Hz 16mSec.  
Minimum,@50% Load  
**Output Voltage Regulation:** +3.3Vdc output : +3.5 Vdc minimum, + 4.5Vdc maximum  
+5Vdc output : +5.5 Vdc minimum, + 6.82Vdc maximum  
+12Vdc output : +13.4 Vdc minimum, + 15.6Vdc maximum  
**Output Rise Time:** 115V-rms/230V-rms 5V 20ms Maximum  
115V-rms/230V-rms 12V 20ms Maximum  
**Ripple & Noise:** 3.3V:50mV p-p  
5V:50mV p-p  
12V1:120mV p-p  
12V2:120mV p-p  
12V3:120mV p-p  
-12V:120mV p-p  
5Vsb:50mV p-p

## ENVIRONMENTAL SPECIFICATION

**TEMP.Range:** Storage Temperature: -20°C to + 80°C  
**MTBF:** The power supply have a minimum predicted MTBF(MIL-HDBK-217) of 100,000 hours of continuous operation at 25°C, maximum-output load, and nominal AC input voltage

This content is subject to change, please refer to specification for more detail. FSP reserve the right to change the content without prior notice